

PCTWORLD INTELLECTUAL PROPERTY ORGANIZATION
International BureauBy Express Mail
No. EV 528957360 US

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : B63H 5/125, 25/42	A1	(11) International Publication Number: WO 98/30440
		(43) International Publication Date: 16 July 1998 (16.07.98)

(21) International Application Number: PCT/NO98/00007


(22) International Filing Date: 9 January 1998 (09.01.98)

(30) Priority Data:
970075 9 January 1997 (09.01.97) NO(71) Applicant (for all designated States except US): ULSTEIN
PROPELLER AS [NO/NO]; N-6065 Ulsteinvik (NO).(71)(72) Applicant and Inventor: GAREN, Rune [NO/NO];
N-6065 Ulsteinvik (NO).(74) Agent: J.K. THORSENS PATENTBUREAU A/S; P.O. Box
9276 Grønland, N-0134 Oslo (NO).

(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, GM, GW, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).

Published*With international search report.**In English translation (filed in Norwegian).*

(54) Title: STEERING AND/OR PROPULSION DEVICE FOR A VESSEL

**(57) Abstract**

A steering and/or propulsion device for a vessel, preferably for installation in the bow portion of the vessel, comprising a propeller nozzle assembly (1) adapted to be rotated 360° about its vertical axis (2). The propeller/nozzle assembly (1) is provided for two active drive positions, one position (ON) below the bottom of the vessel and one position (OO) in a preferably downwardly open channel (3) in the bottom portion of the vessel, whereby the direction of the rotational axis of the propeller is coincident with the axis of the channel. The propeller/nozzle assembly (1) can be reversed also in the upper operative position.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TC	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

Steering and/or propulsion device for a vessel.

The present invention relates to a steering and/or propulsion device for a vessel, preferably for installation in the bow portion of the vessel, comprising a propeller nozzle assembly adapted to be rotated 360° about its vertical axis. Drive power to the propeller and rotational force to the assembly are supplied from devices inside the vessel. The propeller may be of a fixed type or it may be a variable pitch propeller. Propeller/nozzle assemblies of this type are for instance disclosed in the Norwegian patent publication 136038. Such assemblies are commonly called "thrusters".

10

US 3517633 shows crossing channels in a hull, one channel in the longitudinal direction and one channel in the transverse direction. A propeller, which does not work inside a nozzle, has two active positions, one in each channel, but in the same height, whereby the propeller may work in the longitudinal as well as in the transverse direction of the vessel. A downward aperture is situated remote from the propeller, at the rearward exit from the longitudinal channel, for discharge of water for forward propulsion. The propeller is only to work in the two channels. The publication mentions as prior art a so-called "bow thruster", which works in a transverse channel in the vessel, a so-called "retractible thruster", which is lowered prior to use and which can be pulled up when not in use, and a so-called "steerable thruster", which works below the bottom of the vessel and which can be turned 360°.

15
20

US 4294186 shows a propeller which only has one active position, below the bottom of the vessel. The pull-up position is merely a "storing position". This is an assembly of the type "retractible thruster" mentioned above. The propeller can only work in the transverse direction of the vessel in the lowered position. The propeller cannot be turned in any of the positions. Therefore, the propeller must be symmetrical in order to be able to work in both of the rotational directions, i.e. in order to produce drive force in both of the transverse directions of the vessel. The propeller can only work in a single level, below the bottom of the vessel.

25
30

By the present invention a steering and/or propulsion device of the type mentioned introductorily has been provided, and is characterized in that the propeller/nozzle assembly is mounted for movement between two active drive positions, one position below the bottom of the vessel and one position in a transverse channel in the bottom portion of the vessel, whereby the direction of the rotational axis of the propeller is

35

coincident with the longitudinal direction of the channel.

Thus, the present invention relates to a propeller/nozzle assembly which can be situated in two active positions, a first active position pulled up/swung up in a downwardly open
5 channel, and a second active position lowered/swung down below the bottom of the vessel. Both of these positions are active; i.e. that the propeller can work in both of these positions. In the pulled-up/swung-up position the assembly can also be used in shallow water, including to and from a quay or mooring site.

10 In an embodiment of the invention the propeller/nozzle assembly is adapted to be raised and lowered by pivoting the stem of the thruster up and down, respectively, about a horizontal axis, i.e. that the thruster is of a so-called "swing-up" type, whereby the propeller/nozzle assembly prior to the swinging up is pivoted about the stem axis in order that the propeller/nozzle axis be parallel to the channel axis.

15 In another embodiment of the invention the propeller/nozzle assembly is adapted to be raised and lowered by a translatory vertical movement, for instance when the stem is telescopic.

20 The invention will be described more detailed with reference to the accompanying drawings.

Figs. 1 and 3 diagrammatically show a "swing-up" version and a vertically movable
25 version, respectively, of a thruster for conventional use, having only a lower operative position.

Figs. 2 and 4 diagrammatically show an embodiment of the invention in a "swing-up" version and a vertically movable version, respectively, the propeller/nozzle assembly being shown in the two operative positions.

30 In the Figs. 1 and 3 is indicated a thruster in a "swing-up" version and a vertically movable version, respectively, comprising a propeller/nozzle assembly 1 mounted on a stem indicated by its center line 2. Here, the thruster is adapted to be pivoted and moved vertically, respectively, from a lower, operative position O^N to an upper, not
35 operative position S where the propeller/nozzle assembly is hidden in a recess R in the bottom portion of the vessel.

Fig. 2 shows diagrammatically an embodiment of the invention in which a thruster of a "swing-up" version, i.e. a thruster adapted to be pivoted about a horizontal axis A, has two operative positions, a lower operative position O^N below the bottom portion of the vessel and an upper operative position O^O in a downwardly open channel 3 in the bottom portion of the vessel. By turning the propeller/nozzle assembly 1, in the lower operative position, in such a manner that the propeller axis extends parallelly to the axis of the channel 3 the thruster will, when it reaches the upper operative position, mainly function in the same manner as a conventional tunnel thruster. With the thruster embodiment according to the invention it is, however, also possible to reverse the orientation of the propeller/nozzle assembly 1 in the upper operative position O^O . Thus, the propeller/nozzle assembly is oriented in accordance with the desired thrust direction.

The embodiment shown in Fig. 4 departs from that of Fig. 2 in that the thruster is of a so-called vertically movable version, while the functioning in other respects is identical, also as regards the orientation of the propeller/nozzle assembly in the upper operative position.

Driving of the propeller, the turning of the propeller about the stem axis of the thruster and the pivoting, i.e. the vertical movement of the thruster, takes place in a known manner.

Tunnel thrusters of a conventional type have a propeller which works in a tunnel of circular cross section extending through the underwater portion of the vessel, along or transversely of the longitudinal direction of the vessel. In order to achieve equal propeller action in both directions of the tunnel the propeller blades must be shaped with a symmetrical profile, i.e. without curved profile, whereby the action of the propeller is the same for both of the rotational directions. From the same reason it has not been possible to introduce a radial pitch distribution, which among else would have reduced the load on the propeller blade tips. Such a propeller blade shape is in fact contradictory to prevailing circulation theories and well established aero- and hydrodynamical principles. The drawbacks of these known tunnel thruster embodiments are avoided by use of the present invention, in which the propeller/nozzle assembly can be oriented in one direction or in the other direction prior to being brought into the channel, and the propeller blades may, consequently, be shaped with an optimal profile curvature and radial pitch distribution, respectively.


Claims.

1. A steering and/or propulsion device for a vessel, preferably for installation in the bow portion of the vessel, comprising a propeller nozzle assembly (1) adapted to be rotated
5 360° about its vertical axis (2), characterized in that the propeller/nozzle assembly (1) is mounted for movement between two active drive positions, one position (O^N) below the bottom of the vessel and one position (O^O) in a transverse channel (3) in the bottom portion of the vessel, whereby the direction of the rotational axis of the propeller is coincident with the longitudinal direction of the channel.
10
2. A device according to claim 1, characterized in that the propeller/nozzle assembly (1) is adapted to be raised and lowered by being pivoted about a horizontal axis (A) in the bottom portion of the vessel.
- 15 3. A device according to claim 1, characterized in that the propeller/nozzle assembly (1) is adapted to be raised and lowered by being moved vertically.
4. A device according to claim 3, characterized in that the propeller/nozzle assembly (1) is constructed with a telescopically movable stem (2).
20
5. A device according to the claims 1 - 4, characterized in that the channel cross section is dimensioned in such a manner that the propeller/nozzle assembly (1) can be reversed in the channel (3).

FIG. 1

FIG. 1 shows two schematic diagrams of a mechanical assembly. The top diagram is a side view showing a rectangular block 2 with a vertical plate 1 attached to its left side. A dashed rectangle A is shown inside block 2, with a curved arrow indicating rotation. A horizontal line R is shown below block 2, and a vertical line S is shown to the right. A curved arrow indicates rotation around a point O^N . The bottom diagram is a top-down view of the same assembly. Block 2 is a circle with a four-lobed internal pattern. Plate 1 is attached to the left side. A dashed rectangle A is shown inside block 2, with a curved arrow indicating rotation. A horizontal line R is shown below block 2, and a vertical line S is shown to the right. A curved arrow indicates rotation around a point O^N .

FIG. 2



INTERNATIONAL SEARCH REPORT

International application No.

PCT/NO 98/00007

A. CLASSIFICATION OF SUBJECT MATTER

IPC6: B63H 5/125, B63H 25/42

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC6: B63H

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

EPODOC

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	DE 1136907 B1 (PETER JASTRAM), 22 February 1960 (22.02.60), column 5, line 26 - line 66, figures 1, 2 --	1-5
X	US 5522335 A (VERONESI ET AL), 4 June 1996 (04.06.96), figures 1,2, abstract --	1-5
X	US 3550547 A (PLEUGER), 29 December 1970 (29.12.70), figure 1, abstract --	1-5
A	Derwent's abstract, No J-3826 D/36, week J36, ABSTRACT OF SU, 669781 (OVSYANNIKOV M S), 15 December 1980 (15.12.80) --	2

☒ Further documents are listed in the continuation of Box C.

☒ See patent family annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"B" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

20 April 1998

Date of mailing of the international search report

28.04.98

Name and mailing address of the ISA/

Swedish Patent Office

Box 5055, S-102 42 STOCKHOLM

Facsimile No. +46 8 666 02 86

Authorized officer

Björn Salén

Telephone No. +46 8 782 25 00

INTERNATIONAL SEARCH REPORT

International application No.

PCT/NO 98/00007

C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	<p>US 3517633 A (A.W. WANZER), 30 June 1970 (30.06.70)</p> <p style="text-align: center;">-- -----</p>	5

Form PCT/ISA/210 (continuation of second sheet) (July 1992)

INTERNATIONAL SEARCH REPORT

Information on patent family members

02/04/98

International application No.

PCT/NO 98/00007

Patent document cited in search report			Publication date	Patent family member(s)	Publication date
DE	1136907	B1	22/02/60	NONE	
US	5522335	A	04/06/96	NONE	
US	3550547	A	29/12/70	DE 1756689 A FR 1580093 A GB 1226398 A	23/07/70 29/08/69 24/03/71
US	3517633	A	30/06/70	NONE	

This Page Blank (uspto)